



CATALOGUE

Flight proven CubeSat subsystems





CUBESAT PLATFORMS



POWER MODULES



COMMUNICATION



SOLAR PANELS



ANTENNAS



STRUCTURES



ONBOARD COMPUTER




EDUCATIONAL MODULES



CUSTOM MODULES

CLICK ON YOUR DESIRED CATEGORY

R&D powerhouse



In-house mechanical, radio, hardware and software know-how


Mass production capability

Fully closed ISO9001-certified production capabilities capable of producing and qualifying hundreds of subsystems per month





Software-defined buses



1U




1.5U



3U



6U



12U

Engineering support included: ⌚ 10 hours

Lead time: 2 months




Platform Features	1U	1.5U	3U	6U	12U
Bus Mass	850 g	1050 g	2.4–2.9 kg	4.2–4.8 kg	6-8 kg
Available Payload Mass	500 g	950 g	0.5–1.6 kg	7.2–7.8 kg	14-16 kg
Available Payload Volume					
- X	97 mm	97 mm	97 mm	97 mm	197 mm
- Y	97 mm	97 mm	97 mm	197 mm	197 mm
- Z	53 mm	104 mm	173 mm	223 mm	225 mm
Average Payload Power Available	0.7 W	0.9 W	10 W	10–30 W	20-45 W
Available Power Buses	3.3 V, 5 V, battery raw	3.3 V, 5 V, battery raw	3.3 V, 5 V, 6–12 V (configurable), battery raw	3.3 V, 5 V, 6–12 V (configurable), battery raw	3.3 V, 5 V, customizable 6-12 V and Battery raw
Telemetry and Telecommand Data Rate	up to 19.6 kbps	up to 19.6 kbps	up to 19.6 kbps	up to 2 Mbps	up to 2 Mbps
Payload Data Rate	up to 19.6 kbps	up to 19.6 kbps	up to 125 Mbps	up to 125 Mbps	up to 1 Gbps



Flight proven CubeSat platforms

Remarkable satellites

Privileged and confidential





Communication



**X-Band
Transmitter**



**S-Band
Transmitter**



**S-Band
Receiver**



**UHF
Transmitter**

Engineering support included: ⌚ 5 hours

Lead time: 2 weeks



Communication Module Features	UHF Transceiver II	S-Band Transmitter	S-band Receiver	X-Band Transmitter
Frequency Range (Tx)	400–403 MHz or 430–440 MHz	2200–2290 MHz or 2400–2450 MHz	-	7900-8400
Frequency Range (Rx)	400–403 MHz or 430–440 MHz	-	2025-2110 MHz	-
Modulation	2GFSK OOK, GMSK, 2FSK, 2GFSK, (optional)	QPSK, 8-PSK, 16-APSK	BPSK, QPSK	QPSK, 8-PSK, 16-APSK, 32-APSK
Mass	94 g	250 g	180 g	270 g
Maximum Gross Datarate	19.2 kbps	20 Mbps	4 Mbps	150 Mbps
Tx Power	1 W (2W optional)	0.5-2 W (In-flight configurable)	-	0.5-2 W (In-flight configurable)
Sensitivity	up to -121 dBm	-	-95 dBm	-
Frequency Stability	±2.5 ppm	±1.0 ppm	-	±1.0 ppm
Local and Remote Firmware Update	X	X	X	X
Power Supply	-	5 V or 10–24.5 V	5 V or 9–15 V	12–24 V
Internal Memory	-	up to 32 GB	up to 32 GB	up to 32 GB



Flight proven communication


High speed data from space

Privileged and confidential







Antennas



**4x4
X-Band Array**



**2x2
X-Band Array**



**S-Band
Antenna**



**UHF
Antenna**

Engineering support included: ⌚ 5 hours

Lead time: 2 weeks


Antennae Features	UHF	S-Band Antennas (ISM and Commercial)	S-Band Wideband	X-Band 2x2 Patch Arrey	X-Band 4x4 Patch Arrey
Frequency Range	435–438 MHz	2400 - 2450 MHz 2025–2110 MHz	2025-2110 MHz and 2200-2290 MHz	8025–8400 MHz	8025–8400 MHz
Half Power Beam Width	omnidirectional	70 °	70 °	40 °	18 °
Gain	>0 dBi	>7 dBi	5+ dBi	>12 dBi	>16 dBi
Polarization	Circular	Selectable Circular	Right Hand Circular	Right Hand Circular	Right Hand Circular
Mass	85 g	64 g	115 g	23.2 g	53 g
RF Output Power	up to 2 W	up to 4 W	up to 4 W	up to 4 W	up to 4 W



Flight proven antennas

Stable communication

Privileged and confidential





Power Modules



**EPS 2
Power Module**



**EPS 1
Power Module**



**EPS 1
Plus Power Module**

Engineering support included: ⌚ 5 hours




Lead time: 2 weeks



Flight proven power modules


Power and efficiency in orbit

Privileged and confidential







Solar panels




6U Deployable Solar Array




3U Solar Panel



3U Deployable Solar Array



1.5U Solar Panel



1U Solar Panel

Engineering support included: ⌚ 5 hours

Lead time: 2 weeks


Solar Panel Features	1U	1.5 U	3 U	3U Deployable	6U	6U Deployable
Azur Space Solar Cells 3G30A	X	X	X	X	X	X
Maximum Power Efficiency	Up to 30%	Up to 30%	Up to 30%	Up to 30%	Up to 30%	Up to 30%
Maximum Power Generation in LEO	2.4 W	3.6 W	8.4 W	8.4 W	19.4 W	19.4 W
Number of Cells - on the Main Panel	2	3	7	7	16	16
- on the Upper Panel	-	-	-	7	-	16
Possible Cell Configurations	2S1P	3S1P	7S1P	7S1P	4S4P 82AP	4S4P 82AP
Low Power MCU with FRAM	-	-	X	X	X	X
External FRAM	-	-	X	X	X	X
Sun and Temperature Sensors	X	X	X	X	X	X
- Gyroscope (optional)	X	X	X	X	X	X
Actuators - Magnetorquer (optional)	X	X	-	-	-	-
Interfaces - UART	-	-	X	X	X	X
- SPI	X	X	X	X	X	X
- I ² C	-	-	X	X	X	X
- RS-485	-	-	X	X	X	X



Flight proven solar panels


Power and efficiency in orbit

Privileged and confidential






Structures



1U



1.5U



3U



6U

Engineering support included: ⌚ 5 hours

Lead time: 2 weeks

Structure Features**1U****1.5U****3U****6U****Dimensions****- X**

100 mm

100 mm

100 mm

100 mm

- Y

100 mm

100 mm

100 mm

100 mm

- Z

113.5 mm

170.2 mm

340.5 mm

366 mm

Material

Aluminum 6082

Aluminum 6082

Aluminum 6082

Aluminum 6082

Overall Mass

120 g

152 g

290 g

850 g

Roller Switch Options

X

X

X


X



Flight proven structures

Extreme precision and durability

Privileged and confidential





Onboard Computer (OBC)



Engineering support included: ⌚ 5 hours

Lead time: 2 weeks

OBC


Processor	ARM Cortex M7
Program Memory Size	2MB
RAM	256kB
Card Slots	2x MicroSD
Compatibility	Full set of drivers for EnduroSat modules
Double-Redundancy	magnetometer
Clock Type	Real Time Clock
Power Saving	Flexible frequency
Mass	130 g
Interfaces	4x RS-485 or RS-422, 3x UART, 2x I2C, SPI, USB




Flight proven onboard computers

Advanced avionics and data processing

Privileged and confidential




Custom Modules



**Custom 6U Solar
Panel**



**Custom 3U Solar
Panel**



**Custom Patch
Antenna**

[REQUEST A QUOTE](#)

Space Comm System For Education



Engineering support included: ⌚ 5 hours

Lead time: 2 weeks

SPACE IS CLOSER THAN YOU THINK

ENDUROSAT.COM

All photos and images contained in this presentation are **exclusive property of EnduroSat AD**, and are subject to copyright. As such, none of the images and photos may be directly or indirectly published, reproduced, copied, stored, manipulated, modified, sold, transmitted, redistributed, projected, used in any way, or redistributed in any medium without the **explicit permission** of EnduroSat AD.